

## Sample Test Paper

1. A package without body is possible.(T/F)ans:T
2. Subprograms have equal scope as variables.(T/F)
3. Can a [cursor](#) be closed for two times(T/F)ans:F
4. Transaction function can be used in trigger(T/F)ans:F
5. DDL can be used in trigger(T/F)ans:T
6. A trigger name can have the same name as that of its base table name(T/F)ans:T
7. In a PL/SQL block a variable and a table name both are same then which will get highest precedence.
8. Is PL/SQL reserved words can be used in SQL Ans:It can be used with quotation.
9. How to write a single quote in SQL  
i)"" ii)'" iii)'"
10. Can a labeled go to statement goto the inner loop(T/F)ans:F
11. Which are the mandatory parts of PL/SQL procedure.
12. SQL%ISOPEN for implicit cursor is always evaluateto false(T/F)ans:T
13. Any variable not declared in the declare part assigns value .....
14. For cursor %NOTFOUND and for PL/SQL  
NO\_DATA\_FOUND(exception)gives the same result.(T/F)ans:T
15. If exception occured in the exception then it will  
i)raise in the same block  
ii)raise in the outer block  
iii)not raise in the same block
16. PMON command is used for\_\_\_\_\_
17. Select \* from emp where emp\_no=1;  
If exist then dbms\_output\_putline(".....")  
else dbms\_output\_putline("error")

end if;

what will be the output choices are there

18. If for Update lock is absent then will there any error in the following statement

```
select * from emp;
```

choices are there.ans is there will no error

19. Can a inbuilt exception be redefined by a user(T/F)ans:F

20. var table.value%type;

var=5;

```
insert into table(value) values(var);
```

```
for var in reverse 4..6
```

```
loop
```

```
insert into table(value) values(var);
```

```
end loop;
```

```
insert into table(value) values(var);
```

i)56545

ii)56544(ans)

iii)56555

iv)65445

21. can a function overloaded differed by

i)the no of parameters and its type only

ii)their return type

iii)

iv)

22. Raise\_application\_error is used for.....

23. In SQL SGA area the parser [tree](#) and exceptions are stored which are used for multiple applications(T/F)ans:F

24. PRAGMA\_EXCEPTION\_INIT(mssge,code no).....

25. exceptions are executed at

i) compile time

ii) runtime (ans)

26. When a subprocedure will be declared within a procedure?

i) at the end of the declaration

ii) .....

iii) ....

27. Record1 and record2 are declared. each record has two fields with same datatypes.

i) Record1:=Record2;

ii) Record1.field1:=Record2.field1;

iii) Record1.field2:=Record2.field2;

a) only i is legal

b) only ii and iii are legal

c) all are legal

d) none is legal

28. Trigger syntax declaration without the option for each row is

legal (T/F) ans: T

29. Tablespace contains physical data (T/F) ans: T

30. Rowid is a pseudo column of every oracle table (T/F)

31. Lpad and Rpad have default pad character is space (T/F)

32. When %ROWCOUNT is 0 what will happen

i) NO\_DATA\_FOUND exception will raise

ii) %FOUND will be false